



## Specifications

Designed for the primary regulation of high or low cylinder pressure high purity (up to grade 6.0) gases to a constant and stable outlet pressure, the Spec-Master range of plated brass multi-stage regulators covers a variety of applications including gas and liquid chromatography, high purity carrier gases, calibration gases, high purity chamber pressurisation and many more.

## Product Features

- Six Port Configuration
- Front and rear panel mounting facility
- Pipe away safety relief valve for safe venting of exhaust gases
- Reliable encapsulated valve design
- Optional captured bonnet vent kit
- Low wetted surface area for minimal purge requirements
- Full range of inlet connections
- All Spec-Master products are clean room assembled and undergo 100% Helium leak testing
- Designed and manufactured in Norfolk, UK.

## Technical Data

Type	Multi-stage
Inlet Pressure	maximum 300 bar
Outlet Pressure	0-1.5, 0-3.5, 0-10 bar
Materials:	
Body	Nickel plated brass
Valve seat	PCTFE
Diaphragm	316L Stainless steel
Filter	sintered 316L Stainless steel
Inlet Port	1/4 NPT Female
Outlet Port	1/4 NPT Female
Helium Leak Integrity	1x10 <sup>-9</sup> mbar l/s
Temperature range	-20°C to +60°C
Weight	1.9kg

LIT01047 Issue: B Revision: 1