



Specifications

Designed for the secondary regulation of low pressure pipeline high purity (up to grade 6.0) gases to a stable outlet pressure, the Spec-Master range of nickel plated brass pipeline regulators covers a variety of pipeline applications in laboratories, research and development facilities, including gas and liquid chromatography, high purity carrier gases, calibration gases, high purity chamber pressurisation and many more.

Product Features

- Four Port Configuration
- Front and rear panel mounting facility
- Reliable encapsulated valve design
- Optional captured bonnet vent kit
- Low wetted surface area for minimal purge requirements
- All Spec-Master products are clean room assembled and undergo 100% Helium leak testing
- Designed and manufactured in Norfolk, UK.

Technical Data

Type	Single-stage
Inlet Pressure	maximum 40 bar
Outlet Pressure	0-1.5, 0-3.5, 0-10 bar
Materials:	
Body	Nickel plated brass
Valve seat	PCTFE
Diaphragm	316L Stainless steel
Filter	sintered 316L Stainless steel
Inlet Port	1/4 NPT Female
Outlet Port	1/4 NPT Female
Helium Leak Integrity	1x10 ⁻⁹ mbar l/s
Temperature range	-20°C to +60°C
Weight	1.1kg

LIT01043 Issue: B Revision: 2