



### Specifications

The Gas-Arc range of flowmeters are designed primarily for use with shielding gases used in MIG and TIG welding applications. The accuracy of gas flow control is greatly increased by use of a flowmeter and has the added benefit of giving a visual indication of when gas is actually flowing.

### Features

- Range, Gas-Arc flowmeters are capable of supplying 0-14 LPM (0-30CFH) or 0-40 LPM (0-80 CFH).
- Precise flow adjustment, all Gas-Arc flowmeters provide positive, fine flow adjustment that is calibrated at 2 bar (30 psi) inlet pressure.
- Gas, the flowmeters are designed for use on Argon, CO<sup>2</sup> and Argon/CO<sup>2</sup> mixtures.

### Technical Data

|                         |  |
|-------------------------|--|
| Maximum Inlet Pressure: | 4 bar  |
| Outlet Flow:            | 0-14 & 0-40 l/min                              |
| Inlet Connection:       | 3/8 BSP Female RH                              |
| Outlet Connection:      | 3/8 BSP Male RH                                |
| Temperature Range:      | -20°C to +60°C                                 |
| Dimensions:             | Height: 140mm<br>Width: 71mm<br>Diameter: 32mm |
| Weight:                 | 0.25 Kg  |

LIT01091 Issue: A Revision: 1